

※ Ratings: 600KW~2000KW, Voltages: 120V~6600V, Frequency: 60/50Hz,
Revolution: 1800/1500 Rpm, Power Factor: 0.8

GENERATOR SET					MITSUBISHI ENGINE							GEN SET PHYSICAL DATA			
MODEL	STANDBY		PRIME		MODEL	STANDBY		PRIME		FUEL CON-	BORE &	NO.OF	DIMEMSION	WEIGHT	PAD SIZE
	(KW)		(KW)			(HP)		(HP)		SUMPTION	STROKE	CYLINDER			
	50Hz	60Hz	50Hz	60Hz		50Hz	60Hz	50Hz	60Hz	(L/H)(PRIME)	(mm)				
DJG-600MI	520	600	470	545	S6R-PTA	744	865	670	771	150	170×180	I-16	3400×1500×2000	5350	3800×2000
DJG-800MI	680	800	617	725	S12A2-PTA	970	1146	880	980	212.2	150×160	V-12	3800×1700×2100	6420	4200×2100
DJG-1000MI	921	1000	836	909	S12H-PTA	1314	1448	1193	1314	256	150×175	V-12	4000×1800×2400	8100	4400×2200
DJG-1250MI	1124	1250	1020	1135	S12R-PTA	1595	1791	1448	1528	314.7	170×180	V-12	4700×2300×2900	10830	5100×2700
DJG-1350MI	1280	1350	1160	1225	S12R-PTA2	-	1903	-	1729	331	170×180	V-12	4935×2300×2900	10830	5400×2700
DJG-1500MI	1336	1500	1220	1350	S12R-PTAA2	-	2139	-	1940	358	170×180	V-12	5080×2300×2900	13000	5400×2700
DJG-1600MI	1510	1600	1413	1450	S16R-PTA	2131	2279	1994	2067	408.9	170×180	V-16	5600×2750×3000	13000	6000×3100
DJG-1750MI	1689	1750	1536	1590	S16R-PTA2	2359	2547	2145	2312	473.8	170×180	V-16	6000×2750×3000	14000	6400×3100
DJG-2000MI	1818	2000	1616	1818	S12R-PTAA2	2540	2822	2250	2540	504.4	170×180	V-16	6000×2750×3500	15900	6400×3100

• Variety of selectable engines

According to the preference of customers, we provide various products manufactured by the world's most famous brands.

DOOSAN / MITSUBISHI / CUMMINS / HYUNDAI etc

• Heavy-duty Battery Recharger

When recharging batteries, the voltage of the battery can be seen, and by making the recharge capacity larger, the time was shortened.

20~600kW : 5A , 600kW~ : 10A

• Convenient Service Fuel Tank

To prevent rusting in the tank, anticorrosive paint was painted to protect the engine, and the amount of fuel can be easily check by the fuel level.

• Large Capacity Embarked Fuel Tank

The embark capacity was maximized, so that it could be used for more than 4 hours.



•All information is intended for general purpose only. The data given in this table are subject to change without notice.

•Producing with ISO 9001 and ISO 14001 standards